

Technical Specification

FEATURES:

- REMOVABLE CLOTH COVERED GRILLE
- COMBINATION 25/70 VOLT TRANSFORMER
- BUILT IN HANGER
- HIGH DENSITY POLYPROPYLENE ENCLOSURE
- VOICE AND MUSIC REPRODUCTION QUALITY



DESCRIPTION:

Contemporary designed wall speaker for areas that require a stylish appearance. Used for background music and voice paging, the thick walled, high density polypropylene enclosure minimizes vibrations. Using a combination transformer, this speaker can operate on 25 and 70 volt speaker lines. Utilizing the built-in hanger, this speaker may be conveniently mounted on the wall. The speaker is available in white or black with a color coordinated grille.

Specifications:	
<p>SPEAKER 4.5" (11.43 cm)</p> <p>SPEAKER IMPEDANCE 8 Ohm</p> <p>VOICE COIL 1" (2.54 cm)</p> <p>SOUND PRESSURE LEVEL 93 dB @ 1 kHz, 1 W, 1 Meter</p> <p>LINE TRANSFORMER Combination 25/70 Volt</p> <p>TRANSFORMER TAPS 5, 2.5, 1.25, 0.625, and 0.312 Watts</p> <p>FREQUENCY RESPONSE 100 Hz - 10 kHz</p> <p>POWER RATING 5 Watts</p>	<p>FINISH Black or White</p> <p>DIMENSIONS AND WEIGHT 10" (25.4 cm) W x 6.75" (17.15 cm) H x 3.7" (9.40 cm) D Weight: 4.25 (1.91 kg)</p>

Technical Specification

ARCHITECTS' AND ENGINEERS

The Wall Speaker, Model S-527A shall be constructed of a high density polypropylene with a removable color coordinated cloth covered grille. The unit shall contain a single 4.5" (11.43 cm) driver and a multi-tap transformer for 25 or 70 volt speaker lines.

The wattage taps shall be 5, 2.5, 1.25, 0.625 and 0.312 Watts

The frequency response shall be 100 Hz to 10 kHz. The unit shall provide 93 dB with 1 watt, 1 kHz at 1 meter.

The wall speaker shall have an integral hanger molded in the cabinet.

The dimensions shall be 10" (25.4 cm) W x 6.75" (17.15 cm) H and 3.7" (9.40 cm) D. The weight shall be 4.25 lbs (1.9 kg).

Limited Warranty

Clarity warrants its products to be free from defects in materials and workmanship under conditions of normal use and service for a period of one year from the date of shipment. The obligation under this warranty shall be limited to the replacement, repair or refund of any such defective device within the warranty period, provided that:

1. inspection by Clarity indicates the validity of the claim,
2. the defect is not the result of damage, misuse, or negligence after the original shipment,
3. the product has not been in any way repaired by others and that factory sealed units are unopened. (A service charge plus parts and labor will be applied to units defaced or physically damaged).
4. freight charges for the return of products to Clarity are prepaid,
5. all units "out of warranty" are subject to a service charge. The service charge will cover minor repairs (*major repairs will be subject to additional charges for parts and labor*).

This warranty is in lieu of and excludes all other warranties expressed or implied, and in no event shall Clarity be liable for any anticipated profits, consequential damages, loss of time or other losses incurred by the buyer in connection with the purchase, operation or use of the product.

This warranty specifically excludes damage incurred in shipment. In the event a product is received in damaged condition, the carrier should be notified immediately. Claims for such damage should be filed with the carrier involved in accordance with the F.O.B. point.